



Technical Data Sheet

Marking Cable Ties

Worldwide

cannot be reopened

CHARACTERISTICS OF MATERIALS USED

Material:	POLYAMIDE 6.6	NATURAL
Humidity absorption:	2.7 % (23 °C – 50 % relative humidity)	
Temperature range	–40 °C to +85 °C	
Working temperature:	–10 °C to +60 °C	
Tightening temperature:	+110 °C for short time	
Max. admissible point:	+256 °C	
Melting temperature:	27 %	
Limited Oxygen Index (LOI):	5 %	
Corrosion in case of smoke:	UL 94-V2	
Flammability rating:	50.000 volts/mm	
Dielectric strength:		
Resistance against chemicals:	Excellent resistance to aromatic solvents, oils, greases and derivates Good resistance to bases Limited resistance to acids Not resistant to phenols and chlorinated solvents. Halogen free	

Certificates: UL (Underwriters Laboratories): E 86244
DNV-GL (Det Norske Veritas and Germanischer Lloyd): TAE00001DU
R.I.N.A. (Registro Italiano Navale): ELE12017CS
Bureau Veritas: 13190/D0BV
Lloyd's Register Certificate: 09/00025

Raw material used to produce cable ties comply with EC Directives: 2000/53/EC (ELV), 2012/19/EC (WEEE), 1907/2006/EC (REACH) and amendments, 2002/95/EC (RoHS)

Products are tested according to EN IEC 62275 "Cable ties for Electrical Installation".

Recommendation: Keep bag closed after use.

Württembergische Allplastik GmbH
Johannes-Kepler-Str. 12
71083 Herrenberg, Germany
Telefon +49 (0)7032 / 9368 0
Telefax +49 (0)7032 / 9368 98

www.allplastik.com
info@allplastik.com

Certified according to ISO 9001:2015